

PORTABLE LIGHT TOWER

OPTIONS FAMILY



PORTABLE LIGHT TOWER

RG-400-O

RG-400-G

Available in 'Military Green'



Colour for reference only.

PORTABLE LIGHT TOWER
 MOQ 1 (Orange)
 500 (Green)

Available in 'military green'.
 Minimum orders values apply. Green colour for reference only.

DIMENSIONS 310 x 333 x 645mm (folded)
 681 x 580 x 2200mm (unfolded)
WEIGHT 10.4kg (fitting only)
POWER SUPPLY Battery/AC 100-277V
OUTPUT 0-1500lm
RUN TIMES >10hrs (high output, 3 batteries)
OUTPUT (USB) 5V 2A (2 Dock)
BATTERY SYSTEM RG24-100

OPTIONAL TOOLS

RG3-T



TORCH
 MOQ 40

Multifunction Robust torch, floodlights and warning light in one body.

	SPOTLIGHT	FLOODLIGHT
WATTAGE	3W (Max)	6W(Max)
OUTPUT	300lm	400lm
LIGHTING DISTANCE	160m	/
BATTERY DURATION	10 hr (Max) 20hr (Lowest)	6-80hr
BATTERY CAPACITY	3.6V 2500mAh	3.6V 2500mAh
CHARGE TIME	4hr	4hr
IP GRADE	IPX6	IPX6
DIMENSIONS	195 x 41.2 x 43.5mm	195 x 41.2 x 43.5mm
WEIGHT	195g	195g

RG2-HL



HEAD LIGHT
 MOQ 50

6 working modes, 90hrs lighting at extreme mode.

	SPOTLIGHT	FLOODLIGHT
WATTAGE	3W (Max)	6W
OUTPUT	260lm	320lm
DURATION	11/21/9hr	15/35/90hr
BATTERY	3.7V 2000mAh rechargeable lithium battery	3.7V 2000mAh rechargeable lithium battery
CHARGE TIME	2.5hr	2.5hr
DIMENSIONS	75.5 x 52.5 x 47mm	75.5 x 52.5 x 47mm
WEIGHT	95g (without headband)	95g (without headband)

OPTIONAL ACCESSORIES

RG24-100



BATTERY PACK MOQ 12

1 pack to power RG-400 for 30hr at extreme mode.
3 packs to power RG-400 for 10hr at highest output.

RATED POWER	98Wh
RATED VOLTAGE	24.5V
RATED CAPACITY	4.0Ah
WORKING TEMPERATURE	-10°C - 50°C
WORKING HUMIDITY	20 – 95%
DIMENSIONS	113 x 102 x 101mm
WEIGHT	0.9kg

RG-2



DUAL BAY SIMULTANEOUS CHARGER MOQ 12

Charge two batteries at once.

INPUT	100-240V 1.5A
OUTPUT	29.2V 2A
CHARGE TIME (1 x G24-100)	100min
WORKING TEMPERATURE	-0°C - 50°C
WORKING HUMIDITY	20 – 65%
DIMENSIONS	251 x 154 x 153mm
WEIGHT	0.8kg

RG-9



9 BAY SIMULTANEOUS RAPID CHARGER MOQ 1

9 Battery pack carrier supporting RG-400 for several days off-grid operation, rapid charging 2-9 batteries at once.

INPUT	100-240V
OUTPUT	29.2V 4.0A
SIMULTANEOUS CHARGING	
BATTERY QUANTITY	1-9pcs G24-100
CHARGE TIME (1 X RG24-100)	50min
WORKING TEMPERATURE	-0°C - 50°C
WORKING HUMIDITY	20 – 65%
DIMENSIONS	545 x 406 x 261mm
WEIGHT	15.5kg (9pcs G24-100)

RG1-75-56BH



DRIVER MOQ 9

AC input to power RG-400 for 1-1500lm dimmable output, plug and play.

INPUT	100-240V~Max: 0.8A 50/60Hz PF>0.95
	277V Max: 0.29A 50-60Hz (North America only)
OUTPUT	36V - 2.2A
DIMENSIONS	190 x 87 x 49mm
WEIGHT	0.9kg

RECOMMENDED PACKAGES

LIGHT TOWER FLEET ALWAYS FULLY CHARGED BATTERIES



- 3 x RG-400 Light Tower**
- 9 x RG24-100 Battery Pack**
- 1 x RG-9 Charger Case**

CORDLESS OPERATION



- 1 x RG-400 Light Tower**
- 3 x RG24-100 Battery Pack**
- 1 x RG-2 Charger**

CORDLESS + AC



- 1 x RG-400 Light Tower**
- 3 x RG24-100 Battery Pack**
- 1 x RG-2 Charger**
- 1 x RG1-75-56BH Driver**

AC POWERED MAX BRIGHTNESS



- 1 x RG-400 Light Tower**
- 1 x RG1-75-56BH Driver**

WEEKS OFF-GRID OPERATION



- 1 x RG-400 Light Tower**
- 3 x RG-9 Charger Case**